

SOTERIAN SLIM

UAP



Application

Fire resisting, Secured by Design and/or PAS24 timber doorsets

Fixing

Bolted together

Performance

TS008 certified
Certifire CF6025
BSI Kitemarked KM670828
Smoke tested in accordance with BS EN 1634-3
Salt spray tested to BS EN 1670 - Class 5
20,000 cycles

Material

Aluminium (stainless steel Nanocoat option available)

Door thickness (mm)

44 54 & 58

Size (mm)

305x58 (298x98 internal dimension)

Colours

Internal - Silver (PS) / Satin Chrome (SC) / Chrome(C) / Black (BLK) / White (WHT)

External Frame - Silver (PS) / Chrome (C) / Black (BLK) / White (WHT)

Door types

Composite (**CIN**) and Timber (**TIN**)

Fire rating

FD30 (**30**) and FD60 (**60**).
(FD60 only available for timber doors)

Order codes

Internal

TS008/SLIM/ + INT or EXT + Finish

eg. *TS008/SLIM/INT/PS*
Internal in Silver

 5 Regents Drive
Prudhoe
Northumberland
NE42 6PX

 norseal.co.uk

 sales@norseal.co.uk

 01661 830088

Registered in Companies House Cardiff No. 04317595 VAT Reg. No. 733 9466 08